



| | |
|-------------|--|
| Conduit | VINILFLEX "N" |
| Description | Spiral hose with seeable hard PVC spiral inside Code 911093 Colours: black (...01), grey Ral 7035 (...R9) Produced with raw materials according UL94 in class V2 |
| Application | Cable protection hose |
| Temperature | -10°C +65°C |



| Nominal Ø mm | Inner Ø mm | Outer Ø mm | Bending radius mm | Weight g/m |
|--------------------|------------------|------------------|-------------------------|---------------|
| 8 | 8 | 12 | 8 | 50 |
| 10 | 10 | 14.6 | 10 | 70 |
| 12 | 12 | 16.4 | 12 | 75 |
| 14 | 14 | 18.8 | 14 | 90 |
| 15 | 15 | 19.6 | 15 | 95 |
| 16 | 16 | 20.6 | 16 | 100 |
| 18 | 18 | 22.6 | 18 | 110 |
| 19 | 19 | 23.6 | 19 | 118 |
| 20 | 20 | 24.6 | 20 | 125 |
| 22 | 22 | 27.6 | 22 | 150 |
| 25 | 25 | 30.6 | 25 | 180 |
| 28 | 28 | 33.6 | 28 | 210 |
| 30 | 30 | 36 | 30 | 230 |
| 32 | 32 | 38 | 32 | 240 |
| 35 | 35 | 41 | 35 | 280 |
| 38 | 38 | 44.2 | 38 | 310 |
| 40 | 40 | 46.4 | 40 | 330 |
| 45 | 45 | 51.8 | 45 | 380 |
| 50 | 50 | 57.2 | 50 | 430 |
| 60 | 60 | 68 | 60 | 560 |

Tolerance on weight : ± 5%

| | |
|----------------------|----------------|
| Last update 26/11/10 | Signature..... |
|----------------------|----------------|