

Sandblast Couplings and Nozzle Holders


Hose Couplings of Nylon

For Hose	h	b	Weight/pc. g	Type No.	Euro
19 x 7 mm	110	51	193	CQP-3/4	27.60
25 x 7 mm	110	51	165	CQP-1	27.60
32 x 8 mm	136	60	222	CQP-2	25.50
38 x 9 mm	136	67	244	CQP-3	34.35
42 x 9/40 x 10 mm	136	71	215	CQP-4	37.92



Female thread Couplings of Nylon

Thread	h	b	Weight/pc. g	Type No.	Euro
G 1 1/4"	63	61	126	CFP	29.37
Coarse thread 50 mm	63	61	107	CPF-50	31.10



Original Rubber Ring for couplings of Nylon

For Coupling	Material	Colour	Shore h. A	∅i	∅a	h	Weight/pc. g	∅	Type No.	Euro
CQP-3/4	Perbunan	black	60°	19	44	27	20	5	SDR-1	4.97
CQP-1	Perbunan	black	60°	25	44	27	17	5	SDR-2	3.58
All other types	Perbunan	black	60°	31.5	44	27	18	5	SDR-3	3.18



Nozzle Holders of Nylon with female thread

For Hose	Thread	h	b	Weight/pc. g	Type No.	Euro
19 x 7 mm	Coarse thread 50 mm	100	49	115	NHP-34	20.00
25 x 7 mm	Coarse thread 50 mm	100	51	93	NHP-1	17.57
32 x 8 mm	Coarse thread 50 mm	120	59	150	NHP-2	17.57
38 x 9 mm	Coarse thread 50 mm	128	66	156	NHP-3	19.48
19 x 7 mm	G 1 1/4"	100	51	109	HEP-34	20.58
25 x 7 mm	G 1 1/4"	100	51	102	HEP-1	19.53
32 x 8 mm	G 1 1/4"	128	59	154	HEP-2	19.53
38 x 9 mm	G 1 1/4"	128	66	166	HEP-3	20.35



Sandblast Throttle Valve with lever stop, without exhaust, both sides tapered male thread

- Extreme reliable execution with throttle of steel

Inlet	Outlet	DN	h	b	∅Hexag.	Weight/pc. g	Type No.	Euro
R 1"	R 1"	16	96	100	37	741	ADA 10 SK	44.34

