

Tubo in PVC plastificato con spirale in acciaio zincato incorporata, per aspirazione e mandata liquidi alimentari.

Soft PVC hose with embedded galvanised steel spiral, for suction and delivery of food liquids.

**SUPERFICI LISCE**  
SMOOTH SURFACE ★ ★ ★ ★ ★

**FLESSIBILITÀ**  
FLEXIBILITY ★ ★ ★ ★

**RESISTENZA ALL'ABRASIONE**  
ABRASION RESISTANCE ★ ★ ★

**TEMPERATURA D'IMPIEGO**  
TEMPERATURE RANGE -5° C + 65° C

**RESISTENZA CHIMICA**  
CHEMICAL RESISTANCE **tabella PVC**

**RESISTENZA ALLO SCHIACCIAMENTO**  
CRUSHING RESISTANCE ★ ★ ★

Idoneo secondo Reg. CE 1935/2004 e Reg. UE 10/2011 al contatto con alimenti che richiedono liquidi simulanti del tipo A B C, prove di migrazione eseguite a 40°C per 24 ore.  
Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

Ø INTERNO Ø I.D.	Ø INTERNO Ø I.D.	Ø ESTERNO Ø O.D.	PESO WEIGHT	RAGGIO CURVATURA BENDING RADIUS	PRESS. ESERCIZIO WORKING PRESS.	PRESS. SCOPPIO BURSTING PRESS.	SOTTOVUOTO VACUUM	LUNG. ROTOLI COIL LENGTH
inc	mm	mm	g/m	mm	bar	bar	m H <sub>2</sub> O	mt
3/8	10	16	155	20	7	21	8,5	60
	12	18	180	25	7	21	8,5	60
	14	20	200	30	6	18	8,5	60
5/8	16	22	225	35	6	18	8,5	60
	18	24,5	280	40	6	18	8,5	60
	20	27	340	50	5	15	8,5	60
7/8	22	29	360	55	5	15	8,5	60
	1	25	33	510	60	5	15	8,5
1 1/4	30	39	600	70	4,5	13,5	8,5	60
	32	41	650	75	4,5	13,5	8,5	60
1 1/2	35	44	730	80	4	12	8,5	60
	38	47	800	90	4	12	8,5	30
1 3/4	40	49,5	870	95	3	9	8,5	30
	45	55	1100	110	3	9	8	30
2	50	60	1200	125	3	9	8	30
	60	72	1800	140	2,5	7,5	8	30
	75	84	2500	200	2	6	7	30
	80	94	2700	220	2	6	7	30
	100	114	3250	300	2	6	7	30



Tubo in PVC plastificato  
Flexible PVC inner hose

Spirale in acciaio  
Steel spiral

