



Technical Datasheet

SAE J30R9 FKM Fueline Hose

Veyance Technologies Europe, d.o.o.
Škofjeloška c. 6, 4000 Kranj, Slovenia
www.goodyear.eu



1. Tube – FPM (FKM); 2. Tie – NBR; 3. Reinforcement – PET braid; 4. Cover – CM (CPE)

Characteristics & Features:

- Low permeation fueline hose for **AUTOMOTIVE** gasoline & diesel applications
- Ready for alternative fuels like **BIODIESEL**; **SOURGAS** resistant
- High flexibility and small bend radius – **Easy to route**
- Operating Temperature: **-40°C to +135°C**, with peaks up to **+150°C**
- Operating Pressures: Up to **10 bar**
- Designed to meet **SAE J30R9** hose specification
- Available as **STRAIGHT** hose
- **EPA & CARB** approved

Size	[INCH]	1/4"	5/16"	3/8"	1/2"	5/8"
ID	[mm]	6,35	7,9	9,5	12,7	15,9
ID Tolerance	[mm]	+/- 0,4			+/- 0,6	
OD	[mm]	12,7	14,3	15,9	19,8	23,8
OD Tolerance	[mm]	+/- 0,6			+/- 0,8	
Max. Working Pressure	[bar]	10				
Burst Pressure	[bar]	65			50	
Min. Bend Radius	[mm]	35	45	60	70	95

Remark: - SAE J30R9 also available as OEM version with aramid yarn (upon request)
- SAE J30R9 also available in metric sizes acc. DIN 73379 (3,2mm, 6mm, 8mm, others possible upon request)