




plug-in fittings and accessories

3166 reducer



ØD1	ØD2		G	L	L1	△kg△
3	4	3166 03 04	8,5	37,5	23,5	0,004
4	6	3166 04 06	8,5	37,5	23,5	0,004
4	8	3166 04 08	8,5	37,5	19	0,004
4	10	3166 04 10	12	44	22,5	0,005
6	8	3166 06 08	10,5	37,5	20	0,004
6	10	3166 06 10	10,5	38	17,5	0,006
6	12	3166 06 12	14,5	46	23	0,007
6	14	3166 06 14	14,5	48	23	0,008
8	10	3166 08 10	13,5	49	28,5	0,009
8	12	3166 08 12	13,5	49	24,5	0,010
8	14	3166 08 14	17	48	23	0,010
10	12	3166 10 12	21,5	56,5	33,5	0,019
10	14	3166 10 14	21,5	58,5	33,5	0,020
12	14	3166 12 14	23,5	58,5	33,5	0,023



3168 increaser



ØD1	ØD2		G	L	L1	△kg△
6	4	3168 06 04	10,5	35	23	0,003
8	6	3168 08 06	13,5	45	31,5	0,005
10	8	3168 10 08	16	42,5	21	0,009
12	10	3168 12 10	19	49	24,5	0,019



This model enables passage from a smaller to a larger tube diameter

3126 blanking plugs



Ø D		G	L	L1	△kg△
3	3126 03 00	6	25	13,5	0,001
4	3126 04 00	4	30	15,5	0,001
6	3126 06 00	8	33	16,5	0,001
8	3126 08 00	10	33	17,5	0,002
10	3126 10 00	12	42	21	0,003
12	3126 12 00	14	45	22	0,004
14	3126 14 00	16	49	23,5	0,005

3122 barbed connector for unequal tube



ØD1	ØD2		ØD3	L	L1	L2	△kg△
4	5	3122 04 05	7	37	25	17	0,003
4	3,2	3122 04 53	5	37	25	17	0,002
6	5	3122 06 05	7	39	25	17	0,004
8	6,3	3122 08 56	8,5	39,5	21	17	0,005
8	8	3122 08 08	10	44,5	26	22	0,005
10	6,3	3122 10 56	8	45	24,5	17	0,005
10	8	3122 10 08	10	50	29,5	22	0,006
12	8	3122 12 08	10	50	26	22	0,008
12	10	3122 12 10	12	48,5	25,5	22,5	0,014
12	12,5	3122 12 62	14,5	57	34	22,5	0,019
14	12,5	3122 14 62	14,5	59,5	34,5	22,5	0,022
14	14	*3122 14 14	16	59,5	34,5	22,5	0,022