



nickel-plated brass accessories

0915 equal female tee, BSP parallel and M5




C		E	G	H	J	$\frac{L}{2}$	Δ_{kg}
M5x0,8	0915 00 19	4	8	11	9	11	0,009
G1/8	0915 00 10	8	13	21	10	21	0,028
G1/4	0915 00 13	11	17	25,5	13	25,5	0,056
G3/8	0915 00 17	11,5	21	28	17	28	0,083
G1/2	0915 00 21	14	26	33,5	21	33,5	0,139
G3/4	0915 00 27	15	31	36,5	27	36,5	0,215

0916-0923 male stud branch tee, female BSP parallel, male BSP taper and M5




C1	C2		E	G	H	J	$\frac{L}{2}$	Δ_{kg}
M5x0,8	M5x0,8	0923 00 19	4	8	11	9	11	0,009
G1/8	R1/8	0916 00 10	8	13	18,5	10	21	0,025
G1/4	R1/4	0916 00 13	11	17	23,5	13	25,5	0,049
G3/8	R3/8	0916 00 17	11,5	21	26	17	28	0,076
G1/2	R1/2	0916 00 21	14	26	31	21	33,5	0,125
G3/4	R3/4	0916 00 27	15	31	36,5	27	36,5	0,187

0917-0924 male stud run tee, female BSP parallel, male BSP taper and M5




C1	C2		E	G	H	J	$\frac{L}{2}$	Δ_{kg}
M5x0,8	M5x0,8	0924 00 19	4	8	11	9	11	0,009
G1/8	R1/8	0917 00 10	8	13	18,5	10	21	0,024
G1/4	R1/4	0917 00 13	11	17	23,5	13	25,5	0,050
G3/8	R3/8	0917 00 17	11,5	21	26	17	28	0,074
G1/2	R1/2	0917 00 21	14	26	31	21	33,5	0,128
G3/4	R3/4	0917 00 27	15	31	36,5	27	36,5	0,187

0927 equal male tee, BSP taper



C		H	J	L	Δ_{kg}
R1/8	0927 00 10	18,5	10	37	0,017
R1/4	0927 00 13	23,5	13	47	0,038
R3/8	0927 00 17	26	17	52	0,057
R1/2	0927 00 21	31	21	62	0,093

0928 male stud branch tee BSP taper, female BSP parallel



C1	C2		H	J	L	Δ_{kg}	
R1/8	G1/8	0928 00 10	8	37	10	21	0,021
R1/4	G1/4	0928 00 13	11	47	13	25,5	0,044
R3/8	G3/8	0928 00 17	11,5	52	17	28	0,066
R1/2	G1/2	0928 00 21	14	62	21	33,5	0,109